



借通用件登记

减速机输入端

减速机输出端

行星减速机技术参数									
Technical parameters of planetary reducer									
描 图	减速比		3	4	5	7	10	MODEL: TBR90	
	Reduction ratio								
	额定扭矩		65	85	90	90	65		
	Rated torque bureau								
	最大扭矩		2.5倍额定扭矩						
校 描	Maximum torque		2.5 times rated output torque						
	额定转速		3000rpm						
	Rated speed		3000rpm						
	最大转速		6000rpm						
签 字	Maximum speed		6000rpm						
	容许径向力		2400N						
	Allowable radial force		2400N						
	容许轴向力		2200N						
日 期	Allowable axial force		2200N						
	工作温度		-10° ~ 90°						
	Working temperature		-10° ~ 90°						
						背隙 back lash			
					≤10arcm in				
输出端 (Output Terminal)									
									
注意事项 (Notice)									
1. 本产品为精密零部件，应放置于干燥的地方保管。 The product is a precise part and it should be stored in a dry place. 2. 装配前应先检查电机与行星减速机各部位连接的尺寸，然后将减速机与电机自然连接。 Before assembling, the size of the connection between the motor and the parts of the gearbox reducer should be checked. Then the reducer is naturally connected to the motor. 3. 禁止使用铁锤等重物击打，从而造成轴向力与径向力过大破坏轴承与齿轮。 It is forbidden to hit with hammer or other heavy objects It can cause damage to bearings and gears.									
行星减速机 Planetary Gearhead Servobox					图样 标记 重量 比例				
					1:1				
TBR90-L1 尺寸图									